

# **DIMMABLE & LINKABLE LED LIGHTS**

## **FOR REFRIGERATED AND AMBIENT APPLICATIONS**



### **SPECIFICALLY DESIGNED FOR PRODUCT DISPLAY APPLICATIONS**

- Lights are compatible with standard TRIAC dimmer controls for LED lighting that are available from most electrical wholesalers – not sold by Component Hardware
- 60-foot maximum linkable length of combined fixtures
- Can be connected using various length linking cables or direct linking connectors
- Operating temperature from -4°F to 105°F (-20°C to 40°C)
- cULus listed for use in damp locations
- Aluminum alloy housing with polycarbonate cover and end caps
- Instant-on, no ballast to warm up
- Super slim, easy to install

### **ENVIRONMENTALLY FRIENDLY / ENERGY EFFICIENT**

- 50,000+ hours rated life; reduces landfill waste; lowers maintenance costs
- Exceeds Federal Energy Act requirement
- Contributes to LEED® energy use reduction credits
- No ultraviolet emission; does not attract insects
- LEDs emit little heat into refrigerated space



**COMPONENT**  
HARDWARE®



# Technical Specifications for LED-RB Series

**COMPONENT**  
HARDWARE



Model	Nominal Length (L)	Initial Lumens	Current Consumption	Watts
LED-RB08-DIM-x	8" (203mm)	280	35mA	4
LED-RB12-DIM-x	12" (305mm)	490	45mA	6
LED-RB18-DIM-x	18" (457mm)	650	75mA	9
LED-RB24-DIM-x	24" (610mm)	880	100mA	12
LED-RB30-DIM-x	30" (762mm)	1070	130mA	15
LED-RB36-DIM-x	36" (915mm)	1280	150mA	18
LED-RB48-DIM-x	48" (1220mm)	1700	180mA	23

## Accessories

Ref.	Model	Description
A	LED-RB-X110	36" (914mm) Long AC Power Cord with 3 Prong Plug
A	LED-RB-X112	48" (1219mm) Long AC Power Cord with 3 Prong Plug
A	LED-RB-X115	72" (1829mm) Long AC Power Cord with 3 Prong Plug
B	LED-RB-X150	18" (457mm) Long AC Power Supply Cord with Tinned Leads
B	LED-RB-X155	36" (914mm) Long AC Power Supply Cord with Tinned Leads
B	LED-RB-X160	72" (1829mm) Long AC Power Supply Cord with Tinned Leads
C	LED-RB-X170	65" (1651mm) Long AC Power Supply Cord with 3A Rated In-Line Switch and a 3 Prong Plug
D	LED-RB-X206	6" (152mm) Linking Cable
D	LED-RB-X212	12" (305mm) Linking Cable
D	LED-RB-X218	18" (457mm) Linking Cable
D	LED-RB-X224	24" (610mm) Linking Cable
D	LED-RB-X236	36" (914mm) Linking Cable
D	LED-RB-X270	70" (1178mm) Linking Cable
E	LED-RB-X300	Linking Connector
N/A	LED-RB-X200	Rotary Mounting Bracket
N/A	LED-RB-X500	Rotary Mounting Bracket with Magnet

